

CHRISTIE SECURE SERIES III LCD PANELS

Government | Security & surveillance | Control rooms

When security is your highest priority, Christie® Secure Series III LCD 4K UHD panels deliver with performance, display integrity, and reliability you can trust 24/7.



TAA-compliant AV
solutions and services



Engineered for critical security environments, Secure Series III is a trusted choice for control rooms, situation rooms, training centers, and mobile command units where sensitive information requires the highest security.

Unlike conventional commercial displays, Secure Series III is designed with a security-first objective that adheres to strict data protection protocols, making it one of the most secure flat-panel displays available. These displays eliminate common attack surfaces while maintaining the clarity, reliability, and uptime required for critical operations.

Key features

- › Purpose-built secure architecture: With no RF, Wi-Fi or, embedded operating systems to help eliminate common wireless and software-based attack surfaces
- › Signed and encrypted firmware protection: Only authorized software can be installed to prevent tampering and malware intrusion
- › Volatile memory protection: Automatically erases on-screen data at power-down to protect sensitive information and meet statement of volatility requirements
- › Professional 4K UHD quality: Sharp, accurate visuals for mission-critical data and content with 4K UHD resolution and over one billion colors
- › Multi-source viewing with failover: Supports quad-view, picture-in-picture, and picture-by-picture with built-in source switching for continuous visibility



CHRISTIE®

Technical specifications		SUHD55-V3	SUHD65-V3	SUHD75-V3	SUHD86-V3	SUHD98-V3
Display technology	Screen size (inches)	• 55"	• 65"	• 75"	• 86"	• 98"
	Native resolution	• UHD 3840 x 2160				
	Backlight	• Direct LED				
	LED lifespan (to 50%)	• 30,000 hours (typical) to 50% brightness				
	Orientation	• Portrait and landscape				
	Pixel pitch	• 0.315 x 0.315mm	• 0.372 x 0.372mm	• 0.429 x 0.429mm	• 0.493 x 0.493mm	• 0.562 x 0.562mm
	Nominal bezel size (bottom/side/top)	• 21mm/ 21mm/ 21mm	• 20.5mm/20.5mm/ 20.5mm	• 20.5mm/20.5mm/ 20.5mm	• 20.5mm/20.5mm/ 20.5mm	• 28.5mm/28.5mm/ 28.5mm
	Brightness	• 500 nits				
	Contrast ratio	• 1,200:1				
	Viewing angle	• 178° h/v				
	Refresh rate	• 60 Hz				
	Response time	• 8 ms typical				
	Color space (CIE 1931)	• 72% typical				
	Display colors	• 1.07 billion colors				
Video	Video inputs/outputs	• 2 x DisplayPort (version 1.2) • 2 x HDMI (version 2.0) • 2 x HDMI (version 1.4) • VGA / DisplayPort 1.2 Out				
Audio	Audio inputs	• 3.5 mm analog				
	Audio outputs	• 3.5 mm analog SPDIF digital				
Control	Control inputs	• RS-232, LAN, IR extender, Service USB-A				
Power	Power input rating	• 100-240 VAC				
	Power consumption	• 130 W typical (175 W maximum)	• 180 W typical (240 W maximum)	• 220 W typical (300 W maximum)	• 355 W typical (468 W maximum)	• 440 W typical (610 W maximum)
	Standby power	• <=0.14 W	• 0.15 W		• 0.4 W	• 0.37 W
Environment	Operating temperature	• 0–40 C (0–104 F)				
	Storage temperature	• -20–60 C (-4–140 F)				
	Operating humidity	• 10–80% RH				
Physical	Dimensions (WxHxD)	1253.6 x 724.3 x 75 mm	1471.5 x 846.5 x 87 mm	1692.7 x 971 x 87 mm	1944.2 x 1115.2 x 87.2 mm	2218.8 x 1274.3 x 91.7 mm
	Net weight	• 20.3 kg (44.7 lbs)	• 27.7 kg (61 lbs)	• 36 kg (79 lbs)	• 51 kg (112 lbs)	• 67 kg (148 lbs)
	Gross weight	• 26 kg (57 lbs)	• 35 kg (77 lbs)	• 45 kg (99 lbs)	• 63 kg (139 lbs)	• 84 kg (185 lbs)
	Mounting	• VESA 400 x 400, M8	• VESA 600 x 600, M8	• VESA 600 x 600 M8	• VESA 800 x 600 M8	• VESA 1000 x 400 M8 (Landscape) • VESA 1000 x 800 M8 (Portrait)
	Runtime	• 24/7 operation				
	Certifications	• TAA-compliant, NDAA-compliant, CB, LVD, CE, cTUVus, FCC, CEC				
Features		• Four window viewing using multi-view feature (Quadview, Picture-in-Picture, Picture-by-Picture) • Anti-glare treatment to reduce reflection and for better visibility • Source switching for fail over to backup input • No radio frequency (RF) capability • ADA-compliant to meet accessibility requirements • 2 x 10 W speakers				
Accessories		• HDMI cable - Black 1,800 mm ± 50 mm • Power cord U.S. type - Black 1,800 mm ± 50 mm • IR receiver • Remote control • Battery				
Warranty		• Three-year standard limited warranty • Contact an authorized Christie representative or the channel partner for extended warranty and more details				

Please refer to the product user manual, available at www.christiedigital.com

For the most current specification information, please visit christiedigital.com

Copyright 2026 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD71801-Secure-III-data-sheet-July-26-EN

